



65-1

Size	Bore B roughbored mm	D mm	F mm	C mm	W mm	Article number	Permissible speed min ⁻¹	Inertia moment kgm ²
B 125/12,5	-	125	50	25	12,5	2471.125.250	14 500	0,0023
B 150/12,5	-	150	60	30	12,5	2471.150.250	12 100	0,0047
B 200/12,5	-	200	65	40	12,5	2471.200.250	9 100	0,0146
B 250/12,5	-	250	100	50	12,5	2471.250.250	7 300	0,0380
B 300/12,5	-	300	120	60	12,5	2471.300.250	6 000	0,080
B 355/12,5	-	355	145	70	12,5	2471.355.250	5 100	0,162
B 430/12,5	50	430	170	85	12,5	2471.430.250	4 200	0,352
B 520/12,5	50	520	210	105	12,5	2471.520.250	3 500	0,790
B 630/25	75	630	250	125	25	2471.630.250	2 900	3,13
B 710/25	95	710	280	140	25	2471.710.250	2 600	5,09
B 800/25	95	800	320	160	25	2471.800.250	2 300	8,42
B 900/25	120	900	360	180	25	2471.900.250	2 000	13,70
B 1000/25	120	1 000	400	200	25	2471.990.250	1 800	21,3

Other sizes of brake discs

For Brake Calipers DV 030 and DH 030, brake discs with diameters ranging from D = 200 mm up to 520 mm are also available with a disc thickness of W = 25 mm.

Material

The Brake Discs are made from GGG-50 (DIN 1693).

Dimensioning

Please refer to the technical points on pages 72 to 74 when dimensioning the brake disc size.

Any questions? Please contact us.

Morskate Aandrijvingen BV

Oosterveldsingel 47A
7558 PJ Hengelo (Ov)
The Netherlands

NL

T +31 (0)74 - 760 11 11
info@morskateaandrijvingen.nl
www.morskateaandrijvingen.nl

DE

T +49 692 - 222 34 95
info@morskateantriebstechnik.de
www.morskateantriebstechnik.de

EN

T +31 (0)74 - 760 11 11
info@morskatedrivetechnology.com
www.morskatedrivetechnology.com