

Stock programme

		Finish bore [mm] according to ISO fit H7 / feather keyway with thread according to DIN 6885 sheet 1 - JS9																																
Size	Hub type	un/pilot bored	Ø2	Ø3	Ø4	Ø5	Ø6	Ø6.35	Ø7	Ø8	Ø9	Ø9.5	Ø10	Ø11	Ø12	Ø14	Ø15	Ø16	Ø18	Ø19	Ø20	Ø22	Ø24	Ø25	Ø28	Ø30	Ø32	Ø35	Ø38	Ø40	Ø42	Ø45		
7	1.1	●			●	●	●																											
	2.0	●		●	●	●	●	●	●																									
	2.8	●		●	●	●	●																											
8	2.8	●		●	●	●	●		●	●																								
	1.0	●				●				●	●		●																					
	1.1	●			●	●	●		●	●		●		●																				
9	2.0	●		●	●	●	●	●	●	●		●	●	●																				
	2.1	●				●				●	●		●	●																				
	2.8	●				●	●			●	●		●	●																				
12	1.0	●				●				●	●		●		●																			
	2.0	●		●	●	●	●	●	●	●		●	●	●	●																			
	2.1	●				●				●	●		●	●																				
13	2.8	●				●				●	●		●	●	●																			
	1.0	●				●				●	●		●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	
	1.1	●				●				●	●		●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	
14	2.0	●		●	●	●	●	●	●	●		●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	
	2.1	●				●				●	●		●	●																				
	2.8	●				●	●			●	●		●	●																				
16	6.0 light					●				●	●		●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	
	6.0 P					●				●	●		●	●																				
	2.8	●				●				●	●		●	●																				
19	1.0	●				●				●	●		●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	
	2.5	●			■					●	●		●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	
	2.6	●				●				●	●		●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	
	2.8	●				●				●	●		●	●																				
	6.0 light					●				●	●		●	●																				
24	6.0 steel					●				●	●		●	●																				
	6.0 P 50					●				●	●		●	●																				
	6.0 P					●				●	●		●	●																				
	1.0	●				●				●	●		●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	
	2.5	●				●				●	●		●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	
28	2.6	●				●				●	●		●	●																				
	2.8	●				●				●	●		●	●																				
	6.0 light					●				●	●		●	●																				
	6.0 steel					●				●	●		●	●																				
	6.0 P					●				●	●		●	●																				
38	1.0	●				●				●	●		●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	
	2.5	●				●				●	●		●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	●	
	2.6	●				●				●	●		●	●																				
	2.8	●				●				●	●		●	●																				
	6.0 light					●				●	●		●	●																				

Taper bores for Fanuc motors:
 GS 19 1:10 Ø11
 GS 24 1:10 Ø16
¹⁾ Type 2.0/2.1

		Finish bores [mm]														
Size	Hub type	Ø28	Ø30	Ø32	Ø35	Ø38	Ø40	Ø42	Ø45	Ø48	Ø50	Ø55	Ø60	Ø65	Ø70	Ø80
42	6.0 light	●		●	●	●		●	●		●					
	6.0 steel	●	●	●	●	●	●	●	●	●	●					
48	6.0 light			●	●	●	●	●	●	●	●					
	6.0 steel			●	●	●	●	●	●	●	●	●				
55	6.0 steel					●	●	●	●	●	●	●	●			
65	6.0 steel						●	●	●	●	●	●	●	●	●	
75	6.0 steel							●	●	●	●	●	●	●	●	●
90	6.0 steel															●

■ = Pilot bored clamping hubs
 ● = Standard bore from stock
 Unbored hubs up to size 65 available from stock
 Other dimensions on request

Morskate®



Any questions? Please contact us.

Morskate Aandrijvingen BV

Oosterveldsingel 47A
7558 PJ Hengelo (Ov)
The Netherlands

NL

T +31 (0)74 - 760 11 11
info@morskateaandrijvingen.nl
www.morskateaandrijvingen.nl

DE

T +49 692 - 222 34 95
info@morskateantriebstechnik.de
www.morskateantriebstechnik.de

EN

T +31 (0)74 - 760 11 11
info@morskatedrivetechnology.com
www.morskatedrivetechnology.com